

A competition wrestling ring for professional wrestlers. The competition wrestling ring is designed for wrestling matches under the rules of WWE. Extra strong ropes core made from PES with PVC covering.


- ▶ The dimension between the ropes is 6 x 6 m (19.8 x 19.8 ft)
- ▶ Elevated padded floor one meter (3.2 feet)
- ▶ Padded floors 2.50 cm (0.98 inches)

International parameters:

All parameters of the wrestling ring are designed to be as close as possible to the parameters of the World Wrestling Federation. The floor of the ring is well cushioned and covered with printed PVC canvas, and it meets the most stringent safety requirements. The surface of the frame is galvanically treated so as to provide exceptional durability and longevity. Other ring parameters are always optional and always depend on the specific order and choice of a promoter for an event.

Safety:

A special feature of this ring is a suspension design that enables the floor to sag about 7 cm. (gallery) The OSB boards that form the floor of the ring are 2.5 cm (0.98 inches) thick. The elevated OSB floor has a padded layer of 2.5 cm (0.98 inches) and a PVC canvas.



BASIC SPECIFICATION

Use: wrestling gala shows

Product code: WRR 6050

Outer size: 6x6m

Inner size between ropes: 5x5m

Frame: double suspension, zinc coated

Height of the floor: 1 m (3,2ft.)

Floor material: OSB boards

Floor boards quantity: 18

Floor padding: 2,5 cm(0,98 in.)

Weight: 1450kg (3.197 lb.)

SHIPPING DIMENSIONS

Free loaded on the truck: 3,3 x 2,2 x 1,6m (10,8 x 7,2 x 5,2 ft.)

Packed in OSB boxes 2 pcs:: 2,3 x 1 x 1,6m (7,5 x 3,2 x 5,2 ft.)

Packed in boxes #2:: 2,5 x 1,3 x 1m (8,2 x 4,2 x 3,2 ft.)

WARRANTY:

Construction:: 5 years

Others:: 2 years except tear and wear